

ORDINANCE NO. 97 - 3

AN ORDINANCE OF PENN TOWNSHIP, SNYDER COUNTY, PENNSYLVANIA, AMENDING THE TOWNSHIP ORDINANCE NO. 85-2, AS AMENDED, REGARDING ROAD STANDARDS, TO REVISE EXHIBIT A TO INCLUDE A REQUIREMENT THAT ALL ROAD CUTS FOR UTILITY LINES, DRAINAGE TILES, AND THE LIKE SHALL BE BACKFILLED WITH CLEAN 2B STONE.

The Board of Supervisors of Penn Township, Snyder County, Pennsylvania enacts and ordains as follows:

SECTION 1. Authority for Ordinance. This Ordinance is adopted in conformance with and pursuant to authority granted by Sections 2316 and 2317 of the Second Class Township Code (53 P.S. §§67316, 67317), and Sections 503 and 509 of the Municipalities Planning Code (53 P.S. §§10503, 10509), each as amended.

SECTION 2. Amendment. Page 2 of 6, of Exhibit A as referenced in Sections 1(c) and 2(c) of Ordinances 87-2 and 93-2, which amended Ordinance No. 85-2, is amended to require "All road cuts for utility lines, drainage tiles and the like shall be backfilled with clean 2B stone.", as set forth in said Page 2 of 6 (rev 6/97) attached.


SECTION 3. Affirmation. This Ordinance to amend Ordinance No. 85-2, as amended by Ordinances Nos. 87-2 and 93-2, shall affect only page 2 of 6 of Exhibit A as referenced in subsections 1(c) and 2(c) of Section Four. The remaining portions of Ordinance No. 85-2, as amended by Ordinances Nos. 87-2 and 93-2, are affirmed and shall remain in full force and effect.

SECTION 4. Effective Date. This Ordinance shall be in full force and effect 5 days after its enactment.


DULY ENACTED AND ORDAINED this 17th day of June, 1997, by the Board of Supervisors of Penn Township, Snyder County, Pennsylvania, at regular public meeting after proper notice having been given.

PENN TOWNSHIP
Snyder County, Pennsylvania


ATTEST:



Jon Payne, Chairman




Joyce Ulrich, Secretary



Ray W. Klingler, Vice-Chairman

(Township Seal)



Ira Lessman, Supervisor and Roadmaster



00
PENN TOWNSHIP
TYPICAL ROADWAY SPECIFICATIONS
PAGE 2 OF 6

- NOTES: 1. 2A SUBBASE MATERIAL SHALL BE UNIFORM DEPTH AS SPECIFIED.
2. UNSTABLE CUT AND FILL AREAS SHALL BE UNDERCUT AND BACKFILLED WITH CLEAN GRANULAR MATERIAL TO A DEPTH AS REQUIRED TO STABILIZE.
3. ALL ROAD CUTS FOR UTILITY LINES, DRAINAGE TILES, AND THE LIKE SHALL BE BACKFILLED WITH CLEAN 2B STONE (BEFORE THE 2A SUBBASE IS APPLIED).
4. CONSTRUCTION METHODS SHALL BE IN ACCORDANCE WITH PA. DEPARTMENT OF TRANSPORTATION FORM 408.

BITUMINOUS WEARING COURSE - SECTION 400 - 420
BITUMINOUS BASE COURSE - SECTION 300 & 421
EARTHWORK - SECTION 200
EMBANKMENT 206
EXCAVATION AND BORROW EXCAVATION 203, 204 205
PRIME COAT MC-30 OIL 461
SHOULDERS - SECTION 480, 651 & 653
SUBBASE - SECTION 703
SUBGRADE - SECTION 210
SUBSURFACE DRAINAGE 601, 602, 604, 605, 615, 616
SURFACE TREATMENT 480.3, 651

- ROADWAY GRADES:
1. MINIMUM 0.75% GRADE
 2. MAXIMUM 12.0% GRADE
 3. A LEVELING OF APPROXIMATELY 25 FEET NOT EXCEEDING 4.0% SHALL BE PROVIDED AT ALL INTERSECTIONS FROM THE EDGE OF PAVEMENT OF THE INTERSECTING ROAD.
 4. ALL ROADWAY SECTIONS EXCEEDING A 5% GRADE SHALL HAVE PAVED SHOULDERS WITH BITUMINOUS ROLLED EDGES IN ALL CUT AREAS.

ATTACHMENTS TYPICAL SECTIONS:
TYPICAL ROADWAY SECTION
TYPICAL ROADWAY SECTION PAVED SHOULDER AND GUTTER
TYPICAL ROADWAY SECTION OPTIONAL ROADWAY WIDTH
TYPICAL ROADWAY SECTION OPTIONAL ROADWAY WIDTH PAVED SHOULDER AND GUTTER

END